

MATERIAL SAFETY DATA SHEETIssued: August, 1992
REVISED: January 22, 2007**SECTION 1 : PRODUCT INFORMATION**

Product Name: ANTI-SLIPPERY PAINT
Manufacturer: FINEX INC
Address: 110 Boul Bord de l'eau, Valleyfield, J6S 0A2
Emergency Phone: CANUTEC (613) 996-6666
Chemical Family: Acrylic Emulsion Based Water Borne Textured Wall Coating
T.D.G. Classification:

SECTION 2: HAZARDOUS INGREDIENTS

INGREDIENTS	%	TLV	CAS NO.
Ethylene Glycol	3.5		107-21-5
Aluminium silicate	2	n/a	37244-96-5
Titanium Dioxide	<5	10	13463-67-7
Silica	50-60	10	14808-60-7

SECTION 3: PHYSICAL DATA

Physical State: Odour Aqueous Slurry
& Appearance: Odourless, thick aggregate paste
Vapour Pressure: Unknown
Vapour Density: N/A
Evaporation Rate: N/A
Boiling Point: 100 °C
Specific Gravity: PH: 1.4
9-10

SECTION 4 : FIRE & EXPLOSION DATA

Flammability: Nonflammable
Extinguishing Media: N/A
Special Procedures: N/A
Flash Point: N/A
Auto Ignition Temp: N/A
Upper Flammability Limit: N/A
Lower Flammability Limit: N/A
Hazardous Combustion Products: N/A
Explosion Data: No fire or explosion hazards

SECTION 5: REACTIVITY DATA

Conditions Contributing to Instability: Stable
Incompatibility: Very Compatible
Hazardous Polymerization: Will not occur
Reactivity Conditions: None
Hazardous Products of Decomposition: Decomposition products of acrylic polymers

SECTION 6: TOXICOLOGICAL PROPERTIES

Route of Entry: Eyes, Mouth, Skin
Skin Contact: Reddening of skin upon repeated or prolonged contact
Eye Contact: Slight irritation to eyes with direct contact
Inhalation: Over exposure from spray mist may irritate upper respiratory tract
Ingestion: N/A
Effects of Chronic Exposure: N/A

Anti-slippery paint Cont'd
Page 2

Effects of Acute Exposure: **N/A**
TLV: **N/A**

I SECTION 7: PREVENTATIVE MEASURES

Protective Equipment

- Gloves Type: **Impervious gloves**
- Respiratory Type: **Respiratory protection is required when sanding or grinding the finished product because of powdered silica**
- Eye Type: **Safety glasses when spraying**
- Footwear Type: **N/A**
- Clothing Type: **N/A**
- Engineering Controls: **N/A**
- Leak/ Spill: **Wash down with water**
- Waste Disposal: **Same as paint handling procedures**
- Handling Procedures & Equipment Storage: **Avoid skin and eye contact.**
- Needs: **Keep container closed when not in use.**

SECTION 8: FIRST AID MEASURES

Eye Contact: **Irrigate with large amounts of water for at least 15 minutes holding eyelids open. Prompt action is essential for eye contact. Seek medical attention.**

Skin Contact: **Wash exposed areas with clean, fresh water and soap.**

Inhalation: **Move person to fresh air and seek medical attention if irritation persists.**

Ingestion: **Unless unconscious or convulsing, dilute material with water or milk. Do not induce vomiting. Consult physician.**

N/A : Not applicable